



# Model No. 16/2 2-Core Speaker Cable with LS0H Pink Outer Jacket

Cable is metre marked and available in 50m, 100m, 150m, 250, and 300m wooden reels





### **DESCRIPTION**

1.5mmsq. Stranded PACW, 2 Cores, PE Insulation, Rip Cord, LSHF Sheath.

### **APPLICATION**

For the interconnection of control equipment and instruments.

### **CONSTRUCTION**

Conductor

Material: Plain Annealed Copper Wire

Size: 1.5mmsq.

Construction: Stranded (30/0.25mm)

Insulation Material : PE

Nominal O.D: 2.5mm Color: Red, White

Filler

Material: Rip Cord

Sheath

Material: DW9023C LSHF

Max. O.D: 6.6mm Color: Pink

**CPR GRADE Dca** 

### PHYSICAL PROPERTIES

Min. Bend Radius: 66mm

Operating Temperature - 25OC to 90OC

### **ELECTRICAL PROPERTIES**

Max. Conductor DC Resistance @ 20°C, 13.3 $\Omega$ /km

Voltage test: Core to Core, 2.0kV a.c/1min

## **APPLICABLE STANDARD**

EU RoHS Complies 2011/65/EU

EN 60332-1-2

EN 50575 Class Dca



