

USB Digital Audio Converter

(192KHz/24-bit)

AU-D6-192



USB AUDIO

192KHz/24-bit

Optical

The USB Digital Audio Converter is specially designed to take the audio output from a USB Audio Class 2.0 source such as a Laptop or PC and convert it to high quality 2 channel linear PCM optical digital output (TOSLink) for use with an external amplifier or active speakers with a optical digital input.

It utilises a superior USB Audio processor (xMos U8A) with a maximum sampling rate up to 192kHz/24-bit providing an improved frequency response for better audio reproduction. Microsoft Windows and Mac OS X compatible.

SPECIFICATIONS

Input:	1x USB Type B (1x USB (2.0) Audio)
Output:	1x Toslink (1x Optical 2 Channel LPCM)
Power:	USB powered
Dimensions:	25mm (W) x 49mm (D) x 22mm (H)
Gross Weight:	69g
Net. Weight:	32g

FEATURES

- Convert USB Audio Class 2.0 from a Laptop/PC to HD audio and output to an amplifier or active speakers.
- Superior USB audio processor (XMOS U8A) supports up to 192kHz/24-bits sample rates.
- Superior optical module supports up to 192kHz for high resolution digital audio output.
- Supports 2-Channel LPCM: 44.1kHz / 48kHz / 88.2kHz / 96kHz / 176.4kHz / 192kHz
- Simple operation and compact design for use on-the-go or at home
- Compatible with Microsoft Windows XP, Vista, 7, 8, 8.1, 10 (32 & 64-bit) drivers provided
- Compatible with Mac OS X version 10.6.4 or better (USB Audio Class 2.0 is natively supported – no driver required)
- No external power required

