

LTE700 WFAV 25

Art. Number 370579



LTE 700 WFAV 25 - 1 Input - Wideband Masthead Amplifier & Power Supply Kit

- Wolsey LTE 700 Masthead Amplifier Kit
- F-Connector Masthead Amplifier and Power Supply Kit
- 1 Input 1 Output
- 10-25 dB Variable Gain
- Weatherproof Housing
- Fully screened enclosure

Technical Specifications

ORDER INFORMATION

EAN Number 5702663705791

CHARACTERISTICS

Max. Output level (@ -60dB IMD) | dB μ V 102 dB μ V

FREQUENCY RANGE

Band UHF
 Input 1 - frequency | MHz 470...694 MHz
 Input 1 - channels 21...48
 LTE protection @ 700Mhz

GAIN

Input 1 - gain | dB 10...25 dB
 Input 1 - noise figure | dB 1,4 dB

RETURN LOSS

Return Loss | dB 10 Typ dB

ELECTRICAL

Impedance | Ω 75 Ω

OPERATIONAL



Technical Specifications

DC Operating voltage VDC	12 VDC
DC Current consumption mA	100 mA

CONNECTORS

Number of inputs	1
Number of outputs	1

MECHANICAL

Colour	Black
Product Height mm	215 mm
Product Width mm	120 mm
Product Depth mm	60 mm
Packaging Height m	0.060 m
Packaging Width m	0.240 m
Packaging Depth m	0.130 m
Packaging Volume m ³	0.002 m ³
Net Weight kg	0.560 kg
Tara Weight kg	0.060 kg
Total Weight kg	0.620 kg
Remarks	Kit includes WPS 100 Power Supply, 12VDC, 100mA Max Fully screened