


SCP PART#: CTRL-3-LSZH

Description:

UNIVERSAL CONTROL CABLE- LOW SMOKE ZERO HALOGEN-
 2C/14 AWG STRANDED BC + 2C/22 AWG STRANDED BC
 w/AL FOIL SHIELD + DRAIN, EN50575 Eca LSZH JKT- YELLOW
 500FT/152M SPOOL

Standard:

EU RoHS 2011/65 EU Compliant
 EN50575 REACTION TO FIRE CLASS Eca



Construction Characteristics:

Conductor A	Material	Stranded Bare Copper
	Size	14AWG X 2C
	Construction	41/0.254+/-0.004mm
Insulation	Material	PVC
	Min.Thickness	0.24mm
	AVG.Thickness	0.26mm
	Diameter	2.8+/-0.05mm
	Colors	Black & Red
Conductor 1P	Material	Stranded Bare Copper
	Size	22AWG X 2C
	Construction	7/0.254+/-0.004mm
Insulation	Material	FPE
	Min.Thickness	0.56mm
	AVG.Thickness	0.60mm
	Diameter	2.00+/-0.05mm
	Colors	Purple & White
Shield	Drain wire(TC)	7/0.20+/-0.004mm
	Shield	AL Foil
Assembly(2C+1P)	Core wrap	PE Tape
Jacket	Material	LSZH
	Min.Thickness	0.70mm
	AVG.Thickness	0.85mm
	Diameter	8.0+/-0.20mm
	Color	Per request
Bend radius	Min 15D/105mm	

Electrical & Physical Characteristics:

Operating Temperature Range	- 20°C + 75°C
Minimum installation temperature	0°C + 40°C
Conductor Resistance(14AWG)	Max 9.5ohm/km at 20°C
Conductor Resistance(22AWG)	Max 53.5ohm/km at 20°C
14AWG Core/Core Capacitance	20+30pf/m
22AWG Core/Core Capacitance	40+15 pf/m
22AWG Core/Screen Capacitance	90+30 pf/m
Rated Voltage	Max 300Volts
Dielectric Strength	Min AC1.5KV
Marking: STRUCTURED CABLE PRODUCTS --- CTRL-3-LSZH --- 2C/22AWG STR SHIELDED W/DRAIN + 2C/14AWG STR LSZH JKT EN50575:2014 CE Eca RoHS ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***M	
Packaging:	
Approx.Wight(kg)	16.50
Approx.Dimension(mm)	360X330X160
Package	500ft/Spool
Packages per pallet	27