


## WEB 4 x 1.5mm<sup>2</sup> Speaker Cable LSNH Black



**Part Number:** 231022E-LSNH

**Description:** WEB 4 x 1.5mm<sup>2</sup> Speaker Cable LSNH Black

### Product Construction

Conductor Material	:	99.999% Oxygen Free Plain Copper
Conductor Stranding	:	1.5mm <sup>2</sup> , 30/0.25mm
Insulation Material	:	Low Smoke Non-Halogen (LSNH)
Number of Cores	:	4
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Black
Core Colours	:	Red, Blue, Black, White

### Mechanical Characteristics

Overall Diameter	:	8.3mm ± 0.2mm
Temperature Range	Fixed	: -20°C to +70°C
	Flexing	: 0°C to +70°C
Bend Radius	:	15 x Overall Diameter
Weight	:	118 kg/km

### Electrical Characteristics

Inner Conductor DC Resistance	:	≤ 13.3 Ω/km
Voltage Rating	:	300/300V

### Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016



CEDIA<sup>®</sup>  
MEMBER

Publication Date: 05/05/2022  
Revision Number: 1.0  
Written by: GB  
Authorised by: GB

#### **Webro Cables & Connectors Ltd**

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK

Tel: +44 (0)115 9724483 • Fax: +44 (0)115 9461230 • sales@webro.com • [www.webro.com](http://www.webro.com)

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.