


KNX 2pair 0.8mm Screened LSNH White



Part Number: 350303E-LSNH-WHT

Description: KNX 2pair 0.8mm Screened Low Smoke Non-Halogen (LSNH) White

Product Construction

Conductor Material	:	Bare Copper
Conductor Stranding	:	Solid, 1/0.80mm
Insulation Material	:	Polyethylene (PE)
Number of Pairs	:	2
Core Colours	:	Black, Red; Yellow, White
Drain Wire	:	Tinned Copper, 1/0.40mm
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	White

Mechanical Characteristics

Overall Diameter	:	6.6mm ± 0.35mm
Temperature Range	Fixed	-20°C to +70°C
	Flexing	0°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	52 kg/km

Electrical Characteristics

Max. Conductor DC Resistance @ 20°C	:	≤ 36.6 Ω/km
Capacitance, Data	Core to Core	52 pF/m ± 10
	Core to Screen	104 pF/m ± 20
Impedance	:	92 Ω ± 10
Insulation Resistance @ 20°C	:	≥ 200 MΩ*M
Voltage Rating	:	300/500V

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016



CEDIA®
MEMBER

Publication Date: 05/05/2022
Revision Number: 1.0
Written by: GB
Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK

Tel: +44 (0)115 9724483 • Fax: +44 (0)115 9461230 • sales@webro.com • www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.