


WEB 18/22 Red Stripe Lighting Control LSNH



Part Number: 390150E-LSNH-BLU/RED

Description: WEB 18/22 Red Stripe 1pair 22awg Screened + 1pair 18awg LSNH Blue with Red Stripe

Product Construction

Alternative to Lutron	:	GRX-CBL-346S
Data		
Conductor Material	:	Bare Copper
Conductor Stranding	:	22awg, 7/0.25mm
Insulation Material	:	Polyethylene (PE)
Number of Pairs	:	1
Drain Wire	:	Tinned Copper, 24awg
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Core Colours	:	White, Violet

Power

Conductor Material	:	Bare Copper
Conductor Stranding	:	18awg, 7/0.40mm
Insulation Material	:	Polyethylene (PE)
Number of Cores	:	2
Core Colours	:	Black, Red

Overall Construction

Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Blue + Red Stripe

Mechanical Characteristics

Overall Diameter	:	5.0mm ± 0.2mm
Temperature Range	Fixed :	-20°C to +70°C
	Flexing :	0°C to +60°C
Bend Radius	:	10 x Overall Diameter
Weight	:	45 kg/km

Electrical Characteristics

Max. Conductor DC Resistance @ 20°C	: Data	≤ 55.4 Ω/km
	: Power	≤ 21.9 Ω/km
Capacitance, Data	Core to Core	: 82 pF/m ± 15
	Core to Screen	: 165 pF/m ± 25
Insulation Resistance @ 20°C	:	≥ 5000 MΩ*Km
Voltage Rating	:	300/300V

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016



Publication Date: 05/05/2022
 Revision Number: 1.0
 Written by: GB
 Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK

Tel: +44 (0)115 9724483 • Fax: +44 (0)115 9461230 • sales@webro.com • www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.