Technical Document

WEB 12/22 White Stripe Lighting Control LSNH



LASS Eca

Independently

Verified



Part Number: 390152E-LSNH-BLU/WHT

Description: WEB 12/22 1pair 22awg Screened + 1pair 12awg + 1core 18awg LSNH Blue with White Stripe

2

œ

S

2

0

Product Construction

GRX-CBL-46L Alternative to Lutron

Data

Bare Copper **Conductor Material Conductor Stranding** 22awg, 7/0.25mm Polyethylene (PE) Insulation Material

Number of Pairs

Tinned Copper, 24awg Drain Wire Screening 1 Overall Aluminium Foil

>100% Screening 1 Coverage **Core Colours** White, Violet

Power 12awg 18awg

Conductor Material Bare Copper Bare Copper Conductor Stranding 12awg, 7/0.76mm 18awg, 7/0.40mm Insulation Material Polyethylene (PE) Polyethylene (PE)

Number of Cores

Core Colours Black, Red Orange

Overall Construction

Low Smoke Non-Halogen (LSNH) Sheath Material

Sheath Colour Blue + White Stripe

Mechanical Characteristics

Overall Diameter 8.0mm ± 0.2mm Temperature Range Fixed -20°C to +70°C

> Flexing 0°C to +60°C

Bend Radius 10 x Overall Diameter

Weight 80 kg/km

Electrical Characteristics

Max. Conductor DC Resistance @ 20°C : Data ≤ 55.4 Ω/km

> : Power $\leq 5.41 \Omega/\text{km}$ (12awg) \leq 21.9 Ω /km (18awg)

Capacitance, Data Core to Core 75 pF/m ± 15

Core to Screen 125 pF/m ± 25 : \geq 5000 M Ω *Km Insulation Resistance @ 20°C Voltage Rating 300/300V

Certifications & Standards

BS EN 60332-1-2 Flame Retardancy Low Smoke BS EN 61034-2 BS EN 60754-1&2 Halogen Gas

RoHS 3 Compliant Yes **REACH Compliant** Yes

UKCA CPR Classification Eca to BS EN 50575:2014+A1:2016



Publication Date: 05/05/2022

Revision Number: 1.0

Written by: GB Authorised by: GB

Webro Cables & Connectors Ltd
Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK

Tel: +44 (0)115 9724483 • Fax: +44 (0)115 9461230 • sales@webro.com • www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.