



Planet Waves Single Conductor HD Coax Finishing Wire is precision manufactured in the USA to 75 ohm HD standards. All cable features our In=Out™ Technology for pure signal transparency.

This cable is full bandwidth, broadcast quality, with high impedance and low capacitance, enabling you to use it for all Audio/Video applications. The same cable can be used for everything from Component to Composite Video, Analog to Digital Audio, Subwoofers, S/PDIF, even RF applications like HD Satellite and CATV.

Planet Waves HD Finishing Wire is specially designed for rack dressing or exposed drops between A/V devices and display units, such as visible projector runs. It is UL-rated for in-wall installations as well. With a soft TPE jacket, the HD Finishing Wire is especially flexible, making it easy to work within a rack or cabinet. The TPE also provides a clean, polished look and feel to give installations an elegant aesthetic.



Product Specifications

Manufacturing	Made in USA
Standard	75 ohm HD
Sweep Testing	3 Ghz over 100 ft, nominal dB loss
Nominal Capacitance	18.2 pF/ft
Construction	Oxygen-free copper Nitrogen-gas-injected foam PE dielectric
Shielding	100% Shielding with 95% aluminum braid & tin foil sheath
Jacket	TPE
Rating	CM & CL2
Max Pulling Tension	2359 PSI
Max Bend Radius	2.25 inches
Compatibility	Planet Waves Connectors
Jacket Color Options	Black, Red, Blue, Green, White



Part Numbers	Description	Color	UoM
CXSCHD250	HD Coax	Black	250 ft Box
CXSCHD250R	HD Coax	Red	250 ft Box
CXSCHD250G	HD Coax	Green	250 ft Box
CXSCHD250B	HD Coax	Blue	250 ft Box
CXSCHD250W	HD Coax	White	250 ft Box