

Alternative to Belden 9536 6core 24awg LSF Grey



Part Number: 429536E

Description: Alternative to Belden 9536 6core 24awg Overall Foil Screened, LSF Grey Jacket

Product Construction

Alternative to Belden	:	9536
Conductor Material	:	Tinned Copper
Conductor Stranding	:	24awg; 7/0.20mm
Insulation Material	:	Polyvinyl Chloride (PVC)
Number of Pairs	:	6
Core Colours	:	Black, White, Red, Green, Brown, Blue
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Drain Wire	:	Tinned Copper, 24awg Stranded
Sheath Material	:	Low Smoke & Fume (LSF)
Sheath Colour	:	Grey

Mechanical Characteristics

Overall Diameter	:	5.3mm ± 0.20mm
Temperature Range	Fixed	: -20°C to +70°C
	Flexing	: 0°C to +70°C
Bend Radius	:	15 x Overall Diameter
Weight	:	41 kg/km

Electrical Characteristics

Inner Conductor DC Resistance	:	≤ 90.9 Ω/km @ 20°C
Insulation Resistance	:	>200 MΩ*M
Capacitance	Core to Core	: 108 pF/m ± 20
	Core to Screen	: 213 pF/m ± 35
Voltage Rating	:	300V

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016



Publication Date: 15/06/2022
Revision Number: 1.0
Written by: GB
Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK

Tel: +44 (0)115 9724483 • Fax: +44 (0)115 9461230 • sales@webro.com • www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.