


## Alternative to Belden 9501 1pair 24awg LSF Grey



**Part Number:** 429501E

**Description:** Alternative to Belden 9501 1pair 24awg Overall Foil Screen, LSF Grey Jacket

### Product Construction

Alternative to Belden	:	9501
Conductor Material	:	Tinned Copper
Conductor Stranding	:	24awg; 7/0.20mm
Insulation Material	:	Low Smoke & Fume (LSF)
Number of Pairs	:	1
Core Colours	:	Black/Red
Drain Wire	:	Stranded, 24(7)awg
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Sheath Material	:	Low Smoke & Fume (LSF)
Sheath Colour	:	Grey

### Mechanical Characteristics

Overall Diameter	:	3.9mm ± 0.20mm
Temperature Range	Fixed	: -10°C to +70°C
	Flexing	: 0°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	18 kg/km

### Electrical Characteristics

Inner Conductor DC Resistance	:	≤ 97.0 Ω/km @ 20°C
Insulation Resistance	:	>200 MΩ*M
Capacitance	Core to Core	: 131 pF/m ± 20
	Core to Screen	: 243 pF/m ± 35
Voltage Rating	:	300V

### Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016



Publication Date: 31/05/2022  
Revision Number: 1.0  
Written by: GB  
Authorised by: GB

#### **Webro Cables & Connectors Ltd**

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK

Tel: +44 (0)115 9724483 • Fax: +44 (0)115 9461230 • sales@webro.com • [www.webro.com](http://www.webro.com)

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.