


Alternative to Belden 9503 3pair 24awg LSF Grey



Part Number: 429503E

Description: Alternative to Belden 9503 3pair 24awg Overall Foil Screen, LSF Grey Jacket

Product Construction

Alternative to Belden	:	9503
Conductor Material	:	Tinned Copper
Conductor Stranding	:	24awg; 7/0.20mm
Insulation Material	:	Low Smoke & Fume (LSF)
Number of Pairs	:	3
Core Colours	:	Black/Red, Black/White, Black/Green
Drain Wire	:	Stranded, 24(7)awg
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Sheath Material	:	Low Smoke & Fume (LSF)
Sheath Colour	:	Grey

Mechanical Characteristics

Overall Diameter	:	5.6mm ± 0.20mm
Temperature Range	Fixed	: -10°C to +70°C
	Flexing	: 0°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	40 kg/km

Electrical Characteristics

Inner Conductor DC Resistance	:	≤ 97.0 Ω/km @ 20°C
Insulation Resistance	:	>200 MΩ*M
Capacitance	Core to Core	: 131 pF/m ± 20
	Core to Screen	: 243 pF/m ± 35
Voltage Rating	:	300V

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016



Publication Date: 13/08/2022
Revision Number: 1.0
Written by: GB
Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK

Tel: +44 (0)115 9724483 • Fax: +44 (0)115 9461230 • sales@webro.com • www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.