

LTE700 WFAV 622

Art. Number 370583



LTE 700 WFAV 622 - 1 Input - Wideband Masthead Amplifier & Power Supply Kit

- Wolsey LTE 700 Masthead Amplifier Kit
- F-Connector Masthead Amplifier and Power Supply Kit
- 1 Input 6 Output
- 12-22 dB Variable Gain
- Weatherproof Housing
- Fully screened enclosure

Technical Specifications

ORDER INFORMATION

EAN Number 5702663705838

CHARACTERISTICS

Max. Output level (@ -60dB IMD) | dB μ V 83 dB μ V

FREQUENCY RANGE

Band UHF
 Input 1 - frequency | MHz 470...694 MHz
 Input 1 - channels 21...48
 LTE protection @ 700Mhz

GAIN

Input 1 - gain | dB 12...22 dB
 Input 1 - noise figure | dB 2,5 dB

RETURN LOSS

Return Loss | dB 10 Typ dB

ELECTRICAL

Impedance | Ω 75 Ω

OPERATIONAL



Technical Specifications

DC Operating voltage VDC	12 VDC
DC Current consumption mA	100 mA

CONNECTORS

Number of inputs	1
Number of outputs	6

MECHANICAL

Colour	Black
Product Height mm	185 mm
Product Width mm	160 mm
Product Depth mm	60 mm
Packaging Height m	0.060 m
Packaging Width m	0.180 m
Packaging Depth m	0.165 m
Packaging Volume m ³	0.002 m ³
Net Weight kg	0.610 kg
Tara Weight kg	0.070 kg
Total Weight kg	0.680 kg
Remarks	Kit includes WPS 100 Power Supply, 12VDC, 100mA Max Fully screened