



kramer

C-HM/HM/PICO

Ultra-Slim Flexible High-Speed HDMI Cable
with Ethernet

| 4K/60 UHD (4:4:4) | 4K HDR



Kramer's C-HM/HM/PICO is an ultra-slim high-speed HDMI cable with Ethernet. The slim HDMI connector and narrower cable diameter fits more easily into tight spaces behind televisions or in a cabinet. It supports resolutions up to 4K@60Hz (4:4:4)

FEATURES

Max Resolution - 4K@60Hz (4:4:4)

Quality Performance - Kramer's new HDMI cables provide an uncompressed digital link between consumer electronics equipment such as DVD players, set-top boxes and audio/video monitors such as plasma display screens for high-definition TVs

High-Quality Connectors - Slim HDMI connector heads 16.0 mm wide and 8.0mm thick (5/8" wide and 5/16" thick)

Space Saving - A tighter bend radius combined with the low-profile connector can save up to 1" of depth behind the equipment

HDMI Support - Signals up to ultra-HD 4K, HDMI Ethernet Channel, 3D, x.v.Color™, Deep Color, Lip Sync, 7.1 PCM, Dolby TrueHD, DTS-HD, CEC

Available Colors - Black

Varied Selection of Lengths - Available in versions of 0.9 to 3.0m (3, 6 and 10ft)



kramer

TECHNICAL SPECIFICATIONS

Video	Max Resolution for 3-6ft (0.9-1.8m) lengths: 4K60Hz (4:4:4) Max Resolution for 10ft (3m) length: 4K60Hz (4:2:0) Max Data Rate for 3-6ft (0.9-1.8m) lengths: 18Gbps (6 Gbps per channel) Max Data Rate for 10ft (3m) length: 10.2Gbps (3.4 Gbps per channel) HDMI Support HDCP 2.2, EDID, CEC, HDR-10, HLG, Dolby Vision
Audio	Supported Audio Formats: Dolby Digital Plus, Dolby TrueHD, DTS-HD Master Audio™, DVD Audio, SA-CD
PHYSICAL	Connectors: 2 Male HDMI Type A, 24K gold-plated connector Bending radius: 36mm
CONDUCTORS	Diameter: 34AWG(7/0.06) Material: Tinned Copper
SCREENING	Type: Triple shielding
JACKET	Material: PVC Available Colors: Black Diameter: 3.6± 0.15mm
ELECTRICAL	Temperature Rating: 80°C Voltage Rating: 30V Conductor Resistance: 34AWG-1.08KΩ/KM MAX. at 20°C
REGULATORY	Rating (NEC/UL/CSA): VW-1

